

List of Stock Items

Sr.#	Description	QTY
1	<p>PRESSURE GAUGE Model: SP 208 B2P DIAL (NS) : 150 mm (6 inch) Connection : 1/2"NPT-M Range : 0/160 psi Class : 1 Mounting : Vertical Case mat : AISI304 St St Execution : Dry IP67 Window : Glass Wetted parts : AISI316 St St Make: Fantinelli, Italy Complete with Calibration Certificate</p>	02 Nos.
2	<p>PRESSURE GAUGE Model: SP 208 B2P DIAL (NS) : 100 mm (4 inch) Connection : 1/2"NPT-M Range : 0/10 bar Class : 1 Mounting : Vertical Case mat : AISI304 St St Execution : Dry IP67 Window : Glass Wetted parts : AISI316 St St Make: Fantinelli, Italy Complete with Calibration Certificate</p>	02 Nos.
3	<p>PRESSURE GAUGE Model: SP 208 B2P NS : 100 Connection : 1/2"NPT-M Range : -1/+1,5 bar Class : 1 Mounting : Vertical Case mat : AISI304 St St Execution : Dry IP67 Window : Glass Wetted parts : AISI316 St St</p>	01 No.

List of Stock Items

Sr.#	Description	QTY
	Make: Fantinelli, Italy Complete with Calibration Certificate	
4	PRESSURE TRASMITTER (Pencil Type) Model: SE 398 Range 0/10 bar G Class 0,3 Output 4/20mA Wetted parts of AISI316 Ceramic sensor Process connection 1/4"Gas-M* Supply voltage : 9-30 VDC Protection to over voltage peaks up to 36 VDC Connector DIN43650A Protection IP65 Make: Fantinelli, Italy	01 No.
6	Cable CU/XLPE/PVC/SWA/PVC 1 PR x 2.5 mm ² OVERALL SCREEN INSTRUMENT CABLE (300/500V) FLAME RETARDENT SPEC: IEC 60332-1 Make: Universal Cable (M) Berhad Country of Origin: Malaysia Factory Test Report: Available	200 meter
7	Backlight for HMI Model: PS500S-BU00 for GP2500S Make: PROFACE	6 PCS
8	RTD PT100 3-Wire 400 Deg.C (Dia: 10~12 mm; L= 16 mm)	1 PC

List of Stock Items

Sr.#	Description	QTY
9	RTD PT100 3-Wire Dia: 6 mm; L= 6 inch/150mm)	1 PC
10	Digital PID Controller Model: TC-900-301-01-000-0 Dimensions: 96 x 96mm Control output 1: 4 ~ 20mA Control output 2: None Alaram output: 1 Group Transmission output: None Input signal: Thermocouple Operating supply: AC 85 ~ 265V Excitation Power: None Make: ADTEK	1 PC
11	PRESSURE TRASMITTER (Pencil Type) Model: SE 398 Range 0/1 bar G Class 0,3 Output 4/20mA Wetted parts of AISI316 Ceramic sensor Process connection 1/4"Gas-M* Supply voltage : 9-30 VDC Protection to over voltage peaks up to 36 VDC Connector DIN43650A Protection IP65 Make: Fantinelli, Italy	04 No.
12	Temperature Sensor (RTD) With Head mount Transmitter. MODEL = LG200-K-SL24GD120L201Q101-5A Dia = 12 mm Length = 8" (200 mm) ACC=0.5% Connection = 1/2 inch Male Range = 0 to 600 deg.C Material = SS Make =LEEG,China	2
13	Temperature Sensor (RTD) With Head mount Transmitter. MODEL = LG200-K-SL24GD120L101Q101-5A	1

List of Stock Items

Sr.#	Description	QTY
	Dia = 12 mm Length = 4" (100 mm) ACC=0.5% Connection = 1/2 inch Male Range = 0 to 600 deg.C Material = SS Make =LEEG,China	
14	Pressure Guage MODEL = SP208-B2P DN100 x 1/4NPT Range = 0 to 40 bar+ 0 to 580 psi Make = Fantinelli, Italy	4
15	Pressure Guage MODEL = SP208-B2P DN100 x 1/4NPT Range = 0 to 60 psi+ 0 to 4 kg/cm2 Make = Fantinelli, Italy	3
16	Omron Memory Cassette Model: CQMI-ME08K	1
17	Omron Output Card Model: CQMI-OC222	1
18	Conductivity Cell Make: Suntex	1
19	Conductivity Sensor Model: 8-242 Make: Suntex	1
20	Power Supply 24V DC 40A, 1000 Watts.	1

List of Stock Items

Sr.#	Description	QTY
	Make: Weidmuller	
21	Power Supply 24V DC 20A Make: Pheonix	1
22	Suction filter, 297 Micr Model: 387053	1